

SPECIFICATION

Product	Tri-axle 40ft flatbed trailer with side wall
Weight & Size:	
Loading capacity:	40 tons
Overall L*W*H:	12,500*2,500*1,560 mm(side wall height 6,00/ 8,00,1,000,1,200mm. Etc which could be customized)
Frame:	
Material of main beam:	CIMC specified high strength Q345B carbon steel
Side beam:	16# channel steel
Floor:	3 mm checkered plate
Running Gear:	
Axle:	3x13 tons axles , bpw brand
Tire:	315/80R22.5 tubeless (or 12R22.5 or 385/65R22.5.etc) tires with rim , 13 sets , linglong ,triangle or double coin brand
Suspension:	Type1: Heavy duty mechanical suspension Type2: Heavy duty mechanical suspension on rear 2 axles, the 1 st front axle with liftable air suspension Type3: air suspension on 3 axles and the 1 st axle with liftable air suspension Type4: bogie suspension
Leaf spring:	90mm (width)x13mm (thickness) x 10pcs
Landing gear:	JOST E100 or Holland landing gear
Kingpin:	JOST 2 or 3.5 inch bolted type
Brake system:	
Emergency relay valve	Wabco
Air tanker:	2*46L
Brake chamber:	Six-double structure brake chamber
ABS	Optional
Electrical System:	
Receptacle:	7-way socket standard
Voltage:	24 Volt
Lights:	LED
Container Lock:	12 pcs
Color:	Customized
Accessories:	1 pcs tool box + 2 spare tire carriers + optional (fuel tanker, water tanker, basket type spare tire carrier ,stake,front board,side guard)
Reference Pictures:	